


HIGHBAY GEN 5/6



Model	Moc	Lm	Barwa	Kąt Świecenia	V	A/mA	Sprawność	CRI	IP	Rozmiar	Szybkość	Trwałość	ON/OFF	Temp. Pracy	
HBU-G5/6-80	80W	10400 5000K	4000K 6500K	60°90°120°	100-240V AC	1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55	
HBU-G5/6-100	100W	13000 5000K	4000K 6500K	60°90°120°		1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55	
HBU-G5/6-150	150W	19500 5000K	4000K 6500K	60°90°120°		1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55	
HBU-G5/6-180	180W	23400 5000K	4000K 6500K	60°90°120°		1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55	
HBU-G5/6-200	200W	26000 5000K	4000K 6500K	60°90°120°		100-240V AC	1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55
HBU-G5/6-240	240W	31200 5000K	4000K 6500K	60°90°120°			1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55
HBU-G5/6-300	300W	39000 5000K	4000K 6500K	60°90°120°			1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55
HBU-G5/6-400	400W	52000 5000K	4000K 6500K	60°90°120°			1000	0,93	>80	65	400x210	95%<1s	50000	≥50000	-30/+55



NEW
GENERATION
LED

Technology and
innovation

www.isrlight.com